



## Concrete Stain Removal Kit



### Concrete Maintenance Stain Remover Kit

With quart sized containers of LiquiGrind, Densifier, and Stain Defense, the Concrete Maintenance Stain Removal Kit brings all components of the Crete Rx™ Honing and Polishing prescription pathway into one convenient place for spot stain remediation! Stain Removal Kit contains 6 quarts of LiquiGrind, 4 quarts of Densifier, and 2 quarts of Stain Defense.

### Features

- LiquiGrind removes wear and etching
- Densifier strengthens and hardens polished concrete
- Stain Defense penetrates open pores and creates uniform, continuous protective surface
- Convenient kit allows for spot stain remediation

### Available In

**Variety 12 - 32 oz Bottles Item #92411-00**

### Directions for Use

Saturate stained area with wet mop and Betco Densiclean at 0.5 oz. per gallon (1:256). Apply Betco LiquiGrind to fully cover stain and allow to dwell 10 minutes; 250 sq/ft per quart or 1000 sq/ft per gallon. Attach Betco Honing Tool onto drive plate of swing machine (NOTE: Machine pad drivers vary. This may require the use of a velcro pad on pad driver.) Begin Honing Process across entire stained area, overlapping 25% on each pass. A swing machine may require 25-40 passes to remove Stain/Etch. Rewet stain area with LiquiGrind if slurry becomes dry or paste like. Clean and vacuum stained area; if stain is not sufficiently removed, repeat process until stain is removed. Clean area with Betco Densiclean at 0.5 oz. per gallon (1:256). Apply Betco Densifier to honed area, and allow to dry; 2000 sq/ft per gallon or 500 sq/ft per quart. Attach Betco Polishing Tool onto drive plate of swing machine. Polish area, overlapping 25% on each pass, utilizing 25-40 passes as before to remove stain/etch. Clean area thoroughly with mop and bucket or auto scrubber. Apply Betco Stain Defense and allow to dry; 1000 sq/ft per quart or 4000 sq/ft per gallon. "Buff" area with Betco SI Pad to blend area with surrounding floor.

### Applications