Customer Service: 1-888-GO-BETCO
Equipment Tech Support 1-877-856-5954
8AM - 5:30PM EST, Monday - Friday

Betco® Express® Floor Finish with SRT™



Fast Drying - Fast Curing Floor Finish - Max-Cure™ Technology
Betco Express® with SRT™ is a fast drying, fast curing, and extremely low odor floor finish with superior black heel mark resistance. Betco Express with SRT is formulated with Max-Cure Technology™ that utilizes a highly durable, internally cross-linked polymer specially blended to minimize dry and cure times. This labor saving, one of a kind floor finish can be re-coated in as little as 10-15 minutes, allowing up to six coats in an hour.

Features

Fast dry - coats dry in 10 - 15 minutes
Fast cure with Max-Cure™ Technology - up to six coats per hour
Superior black heel mark resistance
Extremely low odor
Low to medium maintenance

Available In

4 - 1 Gal. Bottles Item #65804-00

55 Gal. Drum Item #65855-00

5 Gal Bag in Box Item #658B5-00

Directions for Use

Recommended for use on all types of resilient tile flooring and properly prepared hard surfaces.

RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on Betco® stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 10 - 15 minutes. Elevated temperatures, heavy coats and humidity may extend dry time. A minimum of 6 coats of finish is recommended. NOTE: This product is a self-sealing finish; however, if tile is old, worn or porous, initially applying 1 - 2 coats of a Betco sealer will enhance gloss and long term performance.

ROUTINE MAINTENANCE: Sweep large debris and dust mop. Damp mop or automatic scrub using a Betco floor cleaner. Buff or burnish the floor to enhance gloss as needed. Use Betco® One Step High Speed Cleaner/Restorer to condition the floor and extend the time between top scrub and recoating.

INTERIM MAINTENANCE: Sweep large debris and dust mop the floor. Top scrub the floor using Daily Scrub SC and maroon pad to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 2 - 3 coats of finish as directed above.

Please recycle empty container. NOTE: Slip resistance meets or exceeds (ASTM D 2047-11) James Machine 0.5 minimum.

Tech Specs

Color (dried)	Crystal clear
Color (liquid)	White
Coverage	5,000 square feet/gallon
Fragrance	Mild
Freeze/thaw stability	3 cycles
Gloss (ASTM D 1455-87)	1 coat 80 - 85 2 coats 90 - 95
Heel mark resistance	Very good
Leveling	Excellent
pH	8.1 - 8.9
Powdering resistance	Excellent
Recoat	Excellent
Warranty	2 years
Specific gravity	1.026