

# **Geraldine® Floor Stripper**



## Non-Ammoniated Wax and Finish Stripper

This product quickly unlocks the molecular structure of all types of waterbased floor finishes and sealers. This product also is an excellent heavy duty cleaner. It is great for cutting wax buildup, grease, oil and dirt. The unique chemical elements penetrate, dissolve and lift the wax to the surface to be picked up easily. This product is effective in hot, cold, hard or soft water. Safe for use on all floors not harmed by water.

#### Features

Extended suspension of emulsified particles eliminates costly restripping.

Pleasant - No harsh ammonia or solvent odors. Powerful stripping action.

# Available In

55 Gal. Drum Item #10455-00

5 Gal Bag in Box Item #104B5-00

### Directions for Use

Recommended for water-based acrylic and urethane fortified floors or finishes from all types of resilient tile and hard surfaces. Pre-test in a small area; bleed or discoloration may occur on rubber tile, or asphalt tile. Not Recommended for strip linoleum or sheet vinyl floors. Sweep or dust mop floors or to remove any large debris. Dilute with hot water.

For normal strip dilute 13 oz./gal. or 100 mL/L (1:10) of water. For heavy strip: dilute 25 oz./gal. or 200 mL/L (1:5) of water. Apply solution liberally to floors or surface. Allow 4 - 5 minutes contact time. Be sure to keep surface wet at all times. Agitate with a low speed rotary machine, automatic scrubber or strip machine. Pick up solution with a wet vacuum, automatic scrubber or mop and bucket and thoroughly. Rinse the floors or allow floors to dry completely before applying finish or sealer.

### **Tech Specs**

Oalan	Dial.
Color	Pink
Detergency	Excellent
Emulsification	Excellent
Flash Point	None
Foaming	Moderate
Fragrance	Pleasant
Metal interlock removal	Complete
рН	13.0 - 13.9+
Rinsability	Complete
Solubility in Water	Complete
Viscosity	5 centipoise
Wax removal	Complete
Wetting	Excellent
Warranty	2 years