



Customer Service: [1-888-GO-BETCO](tel:1-888-GO-BETCO)  
8AM - 5PM ET, Monday - Friday

Equipment Tech Support [1-877-856-5954](tel:1-877-856-5954)  
8AM - 4:30PM ET, Monday - Friday

# Drain and Trap Treatment



## Drain and Grease Trap Cleaner and Maintainer

Drain and Trap Treatment contains a blend of probiotics that degrade grease and short and long-chain fatty acids that are the root cause in clogging drain lines and grease traps. The proprietary nutrient package greatly reduces the production of Hydrogen Sulfide odors and other foul odors that are commonly associated with anaerobic (no oxygen) environments.

### [Calculate Your Dosage Rates](#)

#### Features

- NSF International Certified for use in all regulated food processing and food service environments.
- 700 Billion CFU per gallon
- 3.5 x the industry standard CFU per gallon
- Won't damage pipes or traps
- Neutral formula that doesn't contain caustics or acids; safer for the end user
- Can be applied manually or using a Betco® automatic dosing system

#### Available In

**4 - 1 Gal. Bottles Item #260004-00**

**5 Gal. Pail Item #260005-00**

**12 - 32 oz. Bottles Item #260012-00**

**15 Gal. Drum Item #260077-00**

#### Directions for Use

Shake before use. Start using Drain and Grease Trap after grease trap has been pumped. Pour a minimum of one gallon directly in the trap to start treatment. Maintenance Dosing 50 - 100 gallon grease trap capacity: 20-25 ounces daily 100 - 250 gallon grease trap capacity: 25-30 ounces daily 250 - 500 gallon grease trap capacity: 30-35 ounces daily Drain lines Slow Flowing Drains: Shock with 4 oz. daily for the first five days then 2-4 oz. daily Drain Maintenance: Dose during low periods of use shock 4 oz. a week Floor Drains: Shock with 4 oz. per drain weekly Note: Do not subject this product to disinfectants, boiling water or chlorinated products. Improper use or dilution may damage surfaces and increase the risk of health effects. Please consult your local solid waste agency, drain commissioner, or water quality contact for determination on appropriate disposal of unused material. Please recycle empty containers. Wear eye or face protection. Wash hands thoroughly after handling.

#### Tech Specs

Bacteria Count	700 Billion CFU per gallon
Color	Blue
Fragrance	Ocean Breeze
pH	7.0-8.0
Temperature Range	60°F to 90°F
Warranty	2 years