

LiquiShield Concrete Guard



Concrete Guard

LiquiShield is a water based guard formulated to improve gloss while adding substantial protection against stain and etch. It is low odor and easy to apply requiring only two (2) coats at a rate of 3,000-4,000 sq.ft. Per gallon. LiquiShield eliminates the need for floor finish and conventional coatings by resisting scuffs, black marks, and soil. LiquiShield will not peel, flake, or discolor and its breathable formula is ideal for concrete, terrazzo and other porous stone surfaces.

Features

- Low odor and easy to apply
- Resists scuffs, black marks, and soil
- Will not peel, flake, or discolor

Available In

4 - 1 Gal. Bottles Item #167904-00

Directions for Use

Recommended for polished concrete and terrazzo surfaces for extended stain and etch protection. Clean entire area with Betco DensiClean, allow floor to dry prior to application. Apply Betco LiquiShield at proper application rate, 3,000 to 4,000 sq. ft. per gal, with a low-pressure sprayer spread with a microfiber applicator pad or mop and bucket application. Allow to dry to touch, 45 to 60 minutes, then apply second coat using the same procedures. Allow second coat to dry 60 minutes then high speed burnish with Betco Si Burnish Pad. Allow 1 to 2 hours cure time before floor is exposed to full traffic. Allow 24 hours before the use of cleaners on the floor. Maintain floor with Betco Crete Rx DensiClean and Betco Crete Rx Cleaning Pads for maximum protection and shine.

Tech Specs

| | |
|-------------|--------------|
| Color | Opaque White |
| Density | 1.025-1.05 |
| pH | 7.0-9.0 |
| Flash Point | >100C/212F |
| Warranty | 1 year |