

# BIOACTIVE SOLUTIONS™ DT 7



## Drain and Grease Trap Cleaner and Maintainer

BioActive Solutions™ DT 7 contains a blend of microbial species that degrade grease and short and long-chain fatty acids that are the root cause in clogging drain lines and grease traps. The proprietary nutrient package greatly reduces the production of Hydrogen Sulfide odors and other foul odors that are commonly associated with anaerobic environments.

### Features

- 7-strains of microbes for additional performance
- 3.5 x the industry standard CFU per gallon
- Won't damage pipes or traps
- Neutral formula that doesn't contain caustics or acids; safer for the end user
- Can be applied manually or using a Betco® automatic dosing system
- Contains aerobic and facultative anaerobic strains

### Available In

**4 - 1 Gal. Bottles Item #260004-00**

**5 Gal. Pail Item #260005-00**

**12 - 32 oz. Bottles Item #260012-00**

### Directions for Use

Shake before use. Start using BioActive Solutions DT 7 after grease trap has been pumped. Pour a minimum of one gallon directly in the trap to start treatment. Maintenance Dosing 50 - 100 gallon grease trap capacity: 20-25 ounces daily 100 - 250 gallon grease trap capacity: 25-30 ounces daily 250 - 500 gallon grease trap capacity: 30-35 ounces daily Drain lines Slow Flowing Drains: Shock with 4 oz. daily for the first five days then 2-4 oz. daily Drain Maintenance: Dose during low periods of use shock 4 oz. a week Floor Drains: Shock with 4 oz. per drain weekly Note: Do not subject this product to disinfectants, boiling water or chlorinated products.

### Tech Specs

Bacteria Count	700 Billion CFU per gallon
Gram Negatives	Not present
Color	Blue
Fragrance	Ocean Breeze
pH	7.5
Temperature Range	60°F to 90°F
Warranty	2 years