



# LiquiShield Concrete Guard



## Concrete Guard

**New and improved** LiquiShield is a water-based guard formulated to improve gloss while adding substantial protection against stain and etch in the Crete Rx™ Cleaning and Coating prescription pathway. It is low odor and easy to apply requiring only 2-3 coats at a rate of 2,000-3,000 sq.ft. per gallon. LiquiShield eliminates the need for floor finish and conventional coatings by resisting scuffs, black marks, and soil. LiquiShield will not peel, flake, or discolor and its breathable formula is ideal for concrete, terrazzo and other porous stone surfaces.

## Features

Low odor and easy to apply  
Resists scuffs, black marks, and soil  
Will not peel, flake, or discolor

## Available In

**4 - 1 Gal. Bottles Item #167904-00**

## Directions for Use

Recommended for concrete and terrazzo surfaces for extended stain and etch protection. Clean entire area with Betco floor cleaner, allow floor to dry prior to application. Apply Betco LiquiShield at proper application rate, 2,000 to 3,000 sq. ft. per gal, with a microfiber applicator pad or mop and bucket application. Allow to dry to touch, plus 15 minutes, then burnish the floor with a Hair Lite pad, then apply second and third coat using the same procedures. Allow final coat to dry then high speed burnish with Hair Lite Pad. Allow 1 to 2 hours cure time before floor is exposed to full traffic. Allow 24 hours before the use of cleaners on the floor.

## Tech Specs

|             |              |
|-------------|--------------|
| Color       | Opaque White |
| Density     | 1.025-1.05   |
| pH          | 7.0-9.0      |
| Flash Point | >100C/212F   |
| Warranty    | 1 year       |