

PLAYER'S CHOICE 550



Oil-Based Wood Floor Finish

Player's Choice™ from Basic Coatings is a durable oil-modified urethane wood floor finish designed to protect wood floors while providing a rich, attractive appearance.

Features

Rich, attractive oil-based finish
Excellent mar and scuff resistance
For sports, commercial and residential application

Available In

5 Gal. Pail Item #B0693-0512

Directions for Use

Recommended for use in finishing all types of wood floors (gymnasium, sports floors, maple and oak).

FOR NEW OR SANDED FLOORS:

NOTE: Always use a respirator when applying this product.

1. Sand the floor using accepted NWFA or MFMA procedures. All old finish must be removed.
2. Finish sanding with 100 or 120 grit screens.
3. Vacuum all dust and tack the floor with dry cotton towels. Repeat tacking if necessary.
4. Apply 2 coats of a penetrating sealer. Follow recommended application procedures for penetrating sealer.
5. Screen seal coat(s) with 120 grit screens, vacuum and tack with waterless cleaner. Let tack dry 30 - 60 minutes with good ventilation before applying paint or finish.
6. Apply finish. Use a lambs wool applicator first across the grain and then with the grain or use a gravity feed applicator applying the product with the grain of the wood.
7. Two coats of finish are recommended. Apply at 400 - 450 sq.ft./gal.
8. Allow to dry at least 12 hours before recoating. Abrade between coats with maroon top scrub pad or used screens.
9. Let dry at least 72 hours before allowing normal traffic.
10. All paints should be tested prior to use for compatibility and adhesion.

PREVIOUSLY SEALED OR FINISHED FLOORS:

1. Tack floor using cotton towels and waterless cleaner.
2. Screen with 100 grit screens with the grain of the wood.
3. Vacuum all dust and tack the floor with cotton towels and waterless cleaner. Repeat tacking if necessary. Let tack dry before coating.
4. Apply with lambs wool applicator first across the grain and then with the grain or use a gravity feed applicator applying the product with the grain of the wood.
5. Two coats of finish are recommended. Apply at 400 - 450 sq.ft./gal.
6. Allow to dry at least 12 hours before recoating. Abrade between coats with a maroon top scrub pad or used screen.
7. Let dry at least 72 hours before allowing normal traffic.
8. All paints should be tested prior to use for compatibility and adhesion.

NOTE: Do not use on resilient tile. Use waterless cleaner for clean up. Not recommended for floors that have been previously maintained with wax or oil.

Tech Specs

Coverage	450 - 500 sq. ft./gal
Warranty	1 year
Light traffic	24 hours
Color	Light Amber
Recoat	12 - 18 hours
Full cure	72 hours