

# Quick Dry Sealer™ 350 Floor Sealer



## Oil-Based Wood Floor Sealer

Quick Dry Sealer™ 350 is an oil-modified urethane sealer that offers protection to wood floors while providing high gloss and maximum build. Quick Dry Sealer™ 350 penetrates the bare wood and builds the foundation for surface coats and Basic Coatings® oil finishes. VOC Compliant.

### Features

For sports, commercial and residential application  
Seals wood floors  
Fast dry time  
Low 350 VOC

### Available In

**5 Gal. Pail Item #B0628-0512**

### Directions for Use

#### OVER STAINS AND GAME LINE PAINTS

For Stains: Allow stains to dry per manufacturer's directions or longer depending on environmental conditions. Apply 2 coats of a Basic Coatings' Quick Dry Sealer and 2 coats Basic Coatings' finish.

For Game Line Paints: Please refer to Basic Coatings Technical Bulletin, Approved Game Line Paints and Procedure, for proper application and a current list of approved paints.

Note: A TEST BOARD IS RECOMMENDED WITH ANY STAIN/GAME LINE PAINT TO INSURE COMPATIBILITY AND COLOR ACCEPTANCE.

#### SURFACE PREPARATION

1. For new installations, refer to NFWA/MFMA specifications and accepted procedures for acclimation of the wood, floor preparation, and sanding.
2. Before sanding, clean the floor using Basic Coatings' Squeaky Cleaner following label instructions. Cleaning should be done to remove contaminants from the floor.
3. Sand floors using accepted NFWA/MFMA procedures. All old finish must be removed. A NIOSH dust mask should be worn during sanding.
4. Finish sanding with new 120-grit screens is recommended.
5. Vacuum. Tack the floor with 3-4 clean terry cloth tack towels dampened with mineral spirits to remove all dust caused by the sanding and screening process. Tack until no residue collects on the towels. Allow the floor to dry with good ventilation.

FINISH APPLICATION Always maintain adequate ventilation during all phases of the coating and drying process.

1. Stir product well before application.
2. Using Basic Coatings' Applicator or lamb's wool applicator, apply Quick Dry Sealer at the recommended coverage rate. Apply with the grain.
3. Allow to dry, times will vary depending on conditions, usually 4 to 6 hours. Use air blowers to dry corners and dead air spots thoroughly.
4. Abrade floor with new 100 to 120 grit screens is recommended.
5. Vacuum. Tack with 3 - 4 clean terry cloth tack towels dampened with virgin mineral spirits to remove dust. Tack until no dust residue collects on the towels. Allow the floor to dry with good ventilation.
6. Apply second coat or finish coat in the same manner or following manufacturers recommended instructions.

### Tech Specs

Color	Amber
Warranty	1 year
VOC	Less than 350 grams/liter
Coverage	300 - 600 sq. ft/gal (8 - 15 sq. M/L)
Recoat	4 - 6 hours