

# EZ FOG Block SR



## Controlled Release Biological Treatment

EZ FOG Block SR is a longer-lasting high bacterial count solid block formulated with a combination of strains and surfactants ideally suited for a standard system and the breakdown of normal loads and buildup of fats, oils, and grease (FOGs) and other organic compounds.

An excellent solution for applications where the flow rate or water temperature dictate a slowly dissolving product.

### Features

- Simple, easy to use, and provides continuous treatment
- Saves money by reducing the frequency of manual cleanouts/pumpouts, eliminating daily or weekly treatments
- preventing blockages, and lowering grease disposal cost
- Reduces malodors associated with organic waste and sludge
- Available in multiple block sizes for flexibility in dosing

### Available In

**1 - 20 lb. Block/Cs. Item #GTS3051C84**

**12 - 2 lb. Blocks Item #GTS3051C16**

**2 - 10 lb. Blocks Item #GTS3051C11**

**4 - 5 lb. Blocks Item #GTS3051C81**

### Directions for Use

Suspend block in provided netting with rope into area to be treated and replace as needed.

Flow Rate in MGD (GPD)	Block Size (lbs.)
<.05 (50,000)	2
.05-0.25 (50,000-250,000)	5
>0.25-5.0 (250,000-500,000)	10
>0.5 (500,000)	20+

### Grease Trap Capacity Block Size (lbs.)

50-500 gallons	2
500-1000 gallons	5
1000-1500 gallons	10
Over 1500 gallons	20+

Note: Dosing rates are dependent on temperature, pH, and content of the wastewater. The above applications and dosing rates may vary. For problematic systems, please contact your EnviroZyme technical representative.

### Tech Specs

Bacteria Count	5 Billion CFU per gram
Bacterial Type	Non-pathogenic microbes
DSL	Yes
Color	Blue
Fragrance	Characteristic
Gram Negatives	Not present
pH	6.0 - 9.5
Temperature Range	20 - 40 Celsius
Warranty	2 Year
Storage Temperature	10 - 30 Celsius
Storage Humidity	30 - 60%