

Drain & Grease Trap Treatment



Food Service Degradier for a Wide Range of FOG

Drain & Grease Trap Treatment is specially formulated and packaged for direct addition to drains and grease traps in restaurants and commercial buildings. Drain & Grease Trap Treatment contains microorganisms capable of degrading a wide range of FOG blended with natural biological enhancers, micronutrients, and macronutrients to ensure optimum performance.

Features

- Keeps floats clean
- Reduces grease build-up headaches
- Helps to prevent emergency blockages
- Extends life of drain area
- Lowers grease disposal costs
- Reduces odors
- Improves drain field percolation

Available In

5 Gal. Fort Pack Item #GTL309FP5

55 Gal. Drum Item #GTL309D55

Directions for Use

Shake before use. Drain Lines and Down Pipes
 Add 4 oz. of product per 2 inch of pipe size by pouring directly into the drain pipe, starting on the lowest floor and working up at a rate of one floor each day. Do not treat same floor twice, but ensure that all drains on the floor are treated. When the top floor is reached, continue from this floor only. Repeat 2 to 4 times weekly depending on drain usage.

Grease Traps

- Week One - 2 gallons per 500 gallon capacity
- Week Two - 1 gallon per 500 gallon capacity
- Maintenance - 0.5 to 1 gallon per week per 1000 gallon capacity

Septic Tanks

Add 32 oz per 1500 gallon capacity for initial treatment. Thereafter, use 8-10 oz. per month. Apply product directly into a toilet and flush. If septic tank has become clogged, odorous or problematic, add 1 gallon of product directly to the tank through the manhole.

Leach Field/Drain Field

For slow or clogged drain fields, apply 5 gallons directly to the distribution box. Repeat if necessary.

NOTE: Systems with heavy grease loading should be dosed at 1.5X the above rates until the build-up is under control.

Tech Specs

Bacteria Count	200 Billion CFU per gallon
Bacterial Type	Non-pathogenic microbes
DSL	Yes
Color	Green
Fragrance	Citrus
Gram Negatives	Not present
pH	6 - 9.5
Temperature Range	20 - 40 Celsius
Warranty	1 Year
Storage Temperature	10 - 20 Celsius
Storage Humidity	30 - 60