

# Grease & Odor Control



## RTU Grease and Odor Reducer for Drains and Grease Traps

Grease & Odor Control contains microorganisms that are capable of degrading a wide range of oils and greases under aerobic, facultative, and anaerobic conditions.

This biological formula is blended with surfactants to digest organic wastes while simultaneously destroying malodor.

### Features

- Keeps floats clean
- Helps to prevent emergency blockages
- Keeps drains open and free-flowing
- Lowers grease disposal costs
- Reduces odors

### Available In

**275 Gal. Disposable Tote Item #SCL801DSP**

**4 - 1 Gal. Bottles Item #SCL801C4**

**55 Gal. Drum Item #SCL801D55**

### Directions for Use

Shake before use. Drain Lines and Down Pipes: Add 2-4 times weekly depending on drain usage. Begin at the lowest floor, and work upward to top floor, treating only one floor per day. Once the top floor is reached, only treat top floor.

### Pipe Size Dosage

- 2" 4 oz.
- 4" 8 oz.
- 6" 12 oz.
- 8" 16 oz.

Grease Traps: For less than 20 cubic feet capacity, add 4-5 oz. of product daily by pouring in a sink or pipeline closest to the trap. This should be done at night or when traps will be used the least. Flush down with a cup of warm water. For greater than 20 cubic feet capacity, add 8-10 oz. daily, and follow the same procedure.

### Tech Specs

Bacteria Count	200 Billion CFU per gallon
Bacterial Type	Non-pathogenic microbes
DSL	No
Color	White
Fragrance	Citrus
Gram Negatives	Not present
pH	6 - 9.5
Temperature Range	20 - 40 Celsius
Warranty	1 Year
Storage Temperature	10 - 20 Celsius
Storage Humidity	30 - 60