

# StreetShoe® NXT Floor Finish



## Two Component Waterbased Wood Floor Finish

StreetShoe® NXT Waterbased Wood Floor Finish with XL Catalyst is a waterbased system formulated especially for high traffic wood floors. It provides a clear finish that remains unmatched in performance and durability. StreetShoe NXT contains special UV inhibitors that provide even more protection for your floor from the sun's harmful rays.

### Features

- Nano Technology for Extreme Durability
- High Build Formulation
- >150 VOC: LEED compliant
- Fastest cure available; 90% cured in 24 hours
- Apply directly over Stain; Easy to apply
- UV Inhibitor minimizes sunlight-related color changes
- Four sheens (Super Matte, Satin, Semi-Gloss, Gloss)
- Ultimate in durability

### Available In

**Gloss 4 - 1 Gal. F-Style Item #B1664-4312**

**Gloss 5 Gal. Pail Item #B1664-0512**

**Satin 4 - 1 Gal. F-Style Item #B1666-4312**

**Satin 5 Gal. Pail Item #B1666-0512**

**Semi-Gloss 4 - 1 Gal. F-Style Item #B1665-4312**

**Semi-Gloss 5 Gal. Pail Item #B1665-0512**

**Super Matte 4 - 1 Gal. F-Style Item #B1667-4312**

**Super Matte 5 Gal. Pail Item #B1667-0512**

### Directions for Use

#### Tech Specs

Color	Milky White, Dries Clear
Solid Content	31% +/- 2%
Defoaming	Excellent
Leveling	Excellent
Chemical Resistance	Excellent
Odor	Mild
VOC	Below 150 grams/liter
Gloss @ 60°	Gloss >80   Semi-Gloss 45 – 50   Satin 25- 30, Super Matte 10-15
Dry time	2 – 3 hours
Coverage	450 – 650 sq. ft. / Gallon (11 – 16 sq. M/ Liter)
Flash Point	Greater than 200°F (93°C)
Stability	1 year shelf life under proper storage conditions
Clean Up	Water
Packaging	1 U.S. gallon container (4 gallons/case) or 5 U.S. gallon pail
Application	Use Basic Coatings & T-bar, trim pad, roller or brush
Slip Resistance	Meets/Exceeds ASTM D-2047 for Static
Coefficient of Friction	0.5 or better
Warranty	1 year

