

Dissolver™ Floor Polish Remover



Floor Polish Remover

Acrylic Floor Polishes are often used to rejuvenate hardwood floors. These coatings cause uneven or unsightly appearance issues over time and must be removed in order to successfully apply professional urethane coatings. If the Acrylic Test Kit (B9166) has determined that an acrylic floor polish is present, use Basic Coatings& Dissolver™ Floor Polish Remover to strip the acrylic floor polish from the hardwood floor.

Features

Rinse free
Low foaming
No added fragrance or dyes

Available In

4 - 1 Gal. Bottles Item #B0541-0412

Directions for Use

Recommended for removing Green Earth® Floor Finish and conventional floor finishes.

1. Dilute (1:5) 25.6 oz./gal. or 200 mL/L with cold water.
2. Apply solution liberally with mop.
3. Allow 4 - 5 minutes contact time. Be sure to keep surface wet at all times. Agitate with a low-speed rotary machine or automatic scrubber (using a stripping pad or brushes).
4. Pick up solution using a wet vacuum or automatic scrubber and rinse thoroughly.
5. Allow floor to dry completely.

*This product meets Green Seal's environmental standard for industrial and institutional floor care products based on its reduced human and aquatic toxicity and reduced smog production potential.

Tech Specs

Color	Water white
Fragrance	Mild
pH concentrate	10.5
pH at dilution	10.0
Warranty	1 year
Residue at evaporation	None