

Intensive Floor Treatment (I.F.T.) Floor Cleaner



Aggressive Wood Floor Cleaner

I.F.T. is an aggressive cleaner that will easily remove ground-in dirt, body oils, shoe marks, ball scuffs, spilled beverages, etc. I.F.T. is the first step in a two-part cleaning process to prepare floors for the TyKote® Dustfree Refinishing System.

Features

Deep, intensive cleaning.
Removes household waxes, oils and polishes.
Removes dirt and grease in restaurant settings.

Available In

4 - 1 Gal. Bottles Item #B1111-0412

5 Gal. Pail Item #B1111-0512

Directions for Use

1. To prepare the floor for the cleaning process, remove all caked mud, chewing gum, and other debris from the floor. Vacuum the dirt from the floor. Pay special attention to corners.
2. IFT should be diluted using a ratio of 4 parts water to 1 part Intensive Floor Treatment.
3. Soak several clean towels in the solution and wring them until nearly dry. Rubber gloves must be worn to protect hands from skin irritation.
4. Wrap a towel around a push broom and tack the floor. To prevent redeposit of dirt and oil, refold towel using clean sides as needed. Pay special attention to corners.
5. Repeat steps 3-4 in each area of the floor until the entire floor has been cleaned.
6. NOTE: For stubborn surface marks, dirt and shoe marks, use a moderately abrasive nylon pad or sponge moistened with IFT and scour area manually until spot is removed. Follow with a clean water rinse on scrubbed area.
7. Always rinse the floor by damp mopping with clean water and a clean mop until the rinse water is clean or use tack towels with clean water. Pay special attention to corners.
8. Clean the floor again using Basic's Squeaky Cleaner, following the same cleaning procedures described above. (Steps 2-4) Since Squeaky Cleaner does not leave a residue, no clean water rinse is needed after this step. The two cleaners are specifically formulated to remove different types of contaminants from the floor and may not be combined into a single treatment.

ALTERNATE APPLICATION METHOD

1. Prepare a diluted solution of IFT using 4 parts water to 1 part IFT in a mop bucket.
2. Soak string mop in the solution and wring excess out.
3. Mop the floor paying special attention to corners. Re-soak and wring mop frequently. Mop until the entire floor has been cleaned.
4. Always rinse the floor by damp mopping with clean water and a clean mop until the rinse water is clean or use tack towels with clean water. Pay special attention to corners.
5. Clean the floor again using Basic's Squeaky Cleaner, following the same cleaning procedures described above. Since Squeaky Cleaner does not leave a residue, no clean water rinse is needed after this step. The two cleaners are specifically formulated to remove different types of contaminants from the floor and may not be combined into a single treatment.

AUTO-SCRUBBER APPLICATION METHOD

1. If using an automatic scrubber, use a dilution rate of 4 parts water to 1 part IFT along with a white, red, brown or black pad. Make sure squeegees and buffing pads work well. A person with a mop must follow behind the scrubber to pick up any water that is not picked up from the machine. Pay special attention to corners.
2. Flush tank and clean floor with a clean water rinse.
3. Flush tank and clean floor with Basic's Squeaky Cleaner, following the same cleaning procedures as described above.

Tech Specs

Color	Lavender (Light Purple)
Density	8.30 - 8.40 lbs/gallon
Freeze/Thaw	

Freeze/thaw stability	Stable
VOC	At minimum dilution does not exceed 2% by weight
pH	12 – 14
Flash Point	Greater than 200°F
Warranty	2 years