

Rescue Gloss Floor Finish



LVT/Multi-Surface Floor Finish

Innovative floor finishes designed specifically for low and no maintenance floors to protect and extend the life cycle of multiple flooring types. Formulated for maximum adhesion, Rescue floor finishes, part of the Elevate Multiple Surface Floor System works on LVT, sheet vinyl, linoleum, rubber and most other types of flooring types. Rescue is available in Gloss or TruMatte for a natural, matte look.

Features

- Protects low-maintenance wear layer for longer life
- Best Adhesion in Class
- Low Maintenance, durable formula

Available In

Gloss 4 - 1 Gal. Bottles Item #168104-00

5 Gal Bag in Box Item #1681B5-00

Directions for Use

Recommended for use on all types of LVT, sheet vinyl, linoleum, rubber flooring and other properly prepared hard surfaces.

RESTORATIVE MAINTENANCE: Completely remove all old wax, finish and soil from floor surface following strip procedure instructions on Betco's Recover stripper label. Floor surface must be clean, dry and free of residue before finish is applied. Rinse with clean water if necessary. Apply finish in uniform, thin to medium coats using a clean synthetic finish mop, microfiber mop or applicator system. Allow each coat to dry thoroughly before applying additional coats, usually 20 - 30 minutes. Elevated temperatures, heavy coats and humidity may extend dry time.

A minimum of 2 coats of finish is recommended.

Note: Many alternate flooring types may contain a factory finish that can affect coating performance. It is recommended to perform a Top Scrub with Betco's Recover stripper and a maroon pad or equivalent before coating the floor.

ROUTINE MAINTENANCE: Sweep large debris and dust mop. Damp mop or automatic scrub using a Betco floor cleaner. Buff or burnish the floor to enhance gloss as needed (Gloss only). Use Betco's One Step High Speed Cleaner/Restorer to condition the floor and extend the time between top scrub and recoating.

INTERIM MAINTENANCE: Sweep large debris and dust mop. Top scrub the floor using Recover and maroon pad or equivalent to remove the top soiled layers of finish. Floor surface must be clean, dry and free of residue before finish is applied. Apply 1 - 2 coats of finish as directed above. Please recycle empty containers.

Note: Slip resistance meets or exceeds standard, (ASTM D 2047-11) James Machine 0.5 minimum.

Tech Specs

Color (liquid)	Milky white
Coverage	2,000-3,000 sq. ft./gal.
Color (dried film)	Water clear
Drying time	20-30 minutes
Fragrance	Mile
Freeze/thaw stability	3 cycles
Heel mark resistance	Very good
Leveling	Excellent
pH	8.1 - 8.9
Powdering resistance	Excellent
Recoat	Excellent
Warranty	1 year