Customer Service: 1-800-441-1934
8AM - 5:30PM EST, Monday - Friday

Hydroline® Sealer Floor Sealer



Waterbased Wood Floor Sealer

General use, single-component waterbased sealer ideal for sports and residential floors.

Features

Fast drying.
Easy to apply.
Great for maple floors.
VOC compliant.
No catalyst required.

Available In

4 - 1 Gal. Bottles F-Style Item #B0656-4312

5 Gal. Pail Item #B0656-0512

Directions for Use

Read the entire label before using this product. PREPARATION: FOR NEW OR SANDED finish:Prepare the finishusing accepted NOFMA or MFMA procedures. Vacuum all dust andtack with cotton towel. Apply water-based wood sealer followinginstructions on sealer label: 2 coats minimum.

FOR SCREENINGAND RECOATING: Always clean the finish prior to screening. Mixwood finish maintenance cleaner at 32 oz./gal. or 250 mL/L (1:4)with water and tack using a clean towel. Screen using new 100 or120 grit screens, vacuum and tack using a water moistened cottontowel. APPLICATION: Shake or mix container before opening. Whilestirring product, add catalyst slowly and continue mixing for 30seconds. Mix thoroughly and let stand for 5 minutes. Once catalyzed,pot life is 24 hours. Apply at 700 - 850 sq.ft./gal. Allow to drythoroughly (minimum 3 hours between coats depending on conditionswith a maximum of 6 hours). Abrade between coats if 6 hours haselapsed with a maroon top scrub pad or 120 grit screen. Apply 2coats minimum. Allow light traffic after 24 hours, however, it issusceptible to scuffinishng and marring. NOTE: Allow adequate ventilation.Circulate air above the finish. Allow adequate airfinishoorsow for at least 24hours after finishnal coat is applied. Use air conditioners and exhaustfans where available.

MAINTENANCE: DAILY MAINTENANCE: Dustmop using water-based dust mop treatment (see product label foradditional instructions). Dust mop as often as possible, at least onceper day. WEEKLY MAINTENANCE: Tack (deep clean) the finish usingwood finish maintenance cleaner (see product label for additionalinstructions). Tack frequently, but at least once a week. Refer to theWater-Based Wood Coatings Application & Procedure Guide fordetailed instructions. NOTE: Slip resistance meets or exceeds(ASTM D 2047-04) James Machine 0.5 minimum.

Tech Specs

Color	Clear
Coverage	600 sq. ft/gal
Dry time	2 - 3 hours
Recoat Window	2 - 24 hours
Pot life	NA
Warranty	1 year
Light traffic	24 hours
Full cure	7 days
Rugs	2 weeks
VOC	Less than 250 grams/liter