

# PUREMATTE



## Two Component Waterbased Wood Floor Finish

PureMatte™ is a two component matte waterbased wood floor finish specifically formulated to preserve the natural matte look of wood. PureMatte provides commercial durability, excellent wear resistance and clean-ability with a classic matte look.

### Features

- Two Component Durability
- Matte, Low Luster Sheen
- Superior Flow, Leveling and Low Foam Formula
- Preserves Woods Natural Beauty
- Best in Class Soil Resistance and Cleanability
- Exceptional Application Forgiveness and Touch Up Blending

### Available In

**4 - 1 Gal. Bottles F-Style w/Catalyst Item #B1663-4312**

**5 Gal. Pail Item #B1663-0512**

### Directions for Use

#### Tech Specs

Color	Colorless, Water White
Solid Content	30% +/- 2%
Defoaming	Excellent
Leveling	Excellent
Chemical Resistance	Excellent
Odor	Mild
VOC	Below 275 grams/liter
Gloss @ 60°	0-7
Dry time	2 – 3 hours
Coverage	550 – 700 sq. ft. / Gallon (13 – 17 sq. M/ Liter)
Flash Point	Greater than 200°F (93°C)
Stability	1 year shelf life under proper storage conditions
Clean Up	Water
Storage	Do not store above 120°F (49°C)
Packaging	1 U.S. gallon container (4 gallons/case); 5 U.S. gallon pail
Application	Use Basic Coatings & T-bar, trim pad, roller or brush
Slip Resistance	Meets/Exceeds ASTM D-2047 for Static
Warranty	1 year